

NEW “DCP” 4-POST HYDRAULIC REGENERATIVE TRIM PRESS SPECIFICATIONS

S SERIES

Rev 12-22-20

| Model Number | Tonnage | Platen Size TxDXW | Bore & Stroke | Dist Betw Bars | Shut Height | Daylight | Tie bar dia. | Horse power |
|--------------|-------------------|---------------------|---------------|----------------|-------------|----------|--------------|-------------|
| DCP1001S | 100 TON@2600 PSI | 6” x 61” x 73” | 10” x 42” | 36” x 61” | 18” | 60” | 5” | 40 |
| DCP751S | 75 Ton @3000 PSI | 5”x 38”x 62” | 8” x 24” | 26” x 50” | 16” | 40” | 4” | 30 |
| DCP752S | 75 Ton @2000 PSI | 6”x 60”x 62” | 10” x 30” | 48” x 50” | 16” | 46” | 4” | 30 |
| DCP753S | 75 Ton @2000 PSI | 6”x 48”x 96” | 10” x 30” | 36” x 72” | 16” | 46” | 4” | 30 |
| DCP754S | 75 Ton @ 2000 PSI | 7” x 47” x 63” | 10” x 20” | 30” x 52” | 16” | 36” | 4” | 30 |
| DCP755S | 75 Ton @ 2000 PSI | 6” x 42” x 60” | 10” x 34” | 50” X 74” | 11.5” | 34” | 4” | 50 |
| DCP755S | 75 Ton @ 2000 PSI | 6” x 48” x 72” | 10” x 30” | 36” x 60” | 18” | 48” | 4” | 30 |
| DCP756S | 75 Ton @ 3000 PSI | 6” x 48” x 73” | 8” x 48” | 36” x 61” | 18” | 66” | 4” | 30 |
| DCP757S | 75 ton@ 3000 PSI | 5” x 61” x 73” | 8” x 42” | 48” x 60” | 18” | 60” | 4.5” | 30 |
| DCP758S | 75 ton @ 3000 PSI | 6” x 47” x 65” | 8” x 24” | 36” x 54” | 16” | 40” | 4” | 30 |
| DCP621S | 62 Ton @ 2500 PSI | 5”x 42”x 72” | 8” x 24” | 30” x 60” | 15” | 39” | 3 ½” | 30 |
| DCP622S | 62 Ton @ 2500 PSI | 5” x 48” x 72” | 8” x 18” | 36” x 60” | 20” | 38” | 3 ½” | 30 |
| DCP501S | 50 Ton @ 2500 PSI | 4”x 37”x 60” | 7” x 18” | 25” x 48” | 14” | 32” | 3” | 25 |
| DCP502S | 50 Ton @ 2500 PSI | 4”x 42”x 50” | 7” x 20” | 30” x 38” | 14” | 34” | 3 ½” | 25 |
| DCP503S | 50 Ton @ 2500 PSI | 4 ½”x 48”x 60” | 7” x 20” | 36” x 48” | 16” | 36” | 3 ½” | 25 |
| DCP504S | 50 Ton @ 2500 PSI | 5” x 36” x 52” | 7” x 20” | 26” x 42” | 16” | 36” | 3 ½” | 25 |
| DCP401S | 40 Ton @ 2100 PSI | 4”x 32”x 48” | 7” x 18” | 20” x 36” | 14” | 32” | 3” | 20 |
| DCP402S | 40 Ton @ 2100 PSI | 4”x 36”x 48” | 7” x 18” | 24” x 36” | 16” | 34” | 3” | 20 |
| DCP403S | 40 Ton @1200 PSI | 4” x 36” x 48” | 6” x 18” | 26 ½” x 38” | 14” | 32” | 3” | 20 |
| DCP351S | 35 Ton @ 2500 PSI | 3.5”x 32”x 48” | 6” x 16” | 20” x 36” | 14” | 30” | 3” | 20 |
| DCP352S | 35 Ton @ 2500 PSI | 3.5”x 36”x 54” | 6” x 16” | 24” x 42” | 14” | 30” | 3” | 20 |
| DCP353S | 35 Ton @ 2500 PSI | 4” x 36” x 60” | 6” x 24” | 24” x 48” | 12” | 36” | 3” | 20 |
| DCP354S | 35 Ton @ 2500 PSI | 3 ½” x 36” x 48” | 6” x 24” | 24” x 36” | 12” | 36” | 3” | 20 |
| DCP301S | 30 Ton @ 2200 PSI | 3”x 32”x 42” | 6” x 12” | 20” x 30” | 12” | 24” | 3” | 20 |
| DCP302S | 30 Ton @ 2200 PSI | 3”x 36”x 48” | 6” x 12” | 24” x 36” | 12” | 24” | 3” | 20 |
| DCP303S | 30 Ton @ 2200 PSI | 4” x 39” x 46” | 6” x 12” | 30” x 36” | 12” | 24” | 3” | 20 |
| DCP304S | 30 Ton @ 2200 PSI | 4” x 36” x 46” | 6” x 18” | 26” x 36” | 16” | 34” | 3” | 20 |
| DCP305S | 30 Ton @ 2200 PSI | 4” x 30” x 43” | 6” x 24” | 19” x 33” | 12” | 36” | 3” | 20 |
| DCP251S | 25 Ton @ 2600 PSI | 3”x 36”x 45” | 5” x 12” | 26” x 36” | 12” | 24” | 2 ½” | 15 |
| DCP201S | 20 Ton @ 2100 PSI | 2.5”x 28.5” x 40.5” | 5” x 12” | 18” X 30” | 12” | 24” | 2 ½” | 15 |
| DCP202S | 20 Ton @ 2100 PSI | 2.5”x 26”x 32.5” | 5” x 12” | 17” x 24” | 15” | 26” | 2 ½” | 20 |
| DCP203S | 20 Ton @ 2100 PSI | 3.5” x 30.5 x 43 .5 | 5” x 14” | 20” x 33” | 14” | 28” | 2 ½” | 15 |
| DCP151S | 15 Ton @ 1600 PSI | 3.5” x 30.5 x 43 .5 | 5” x 18” | 20” x 33” | 14” | 32” | 2 ½” | 15 |
| DCP152S | 15 Ton@1600 PSI | 3” x 26” x 32.5” | 5” x 12” | 17” x 22” | 12” | 24” | 2 ½” | 15 |
| DCP153S | 15 ton@2500 PSI | 2 ½” x 28” x 28” | 4” x 14” | 20” x 20” | 14 | 28” | 2 ½” | 15 |
| DCP101S | 10 Ton @ 1600 PSI | 2 ½” x 22” x 28” | 3 ¼” x 10” | 16” x 22” | 10” | 20” | 2” | 7.5 |

Made In The USA ! Quality By American Tradesmen

Die Cast Press Mfg. Co., Inc. 56480 Kasper Drive – Paw Paw MI 49079 Phone (269) 657-6060 or Fax (269) 657-9302

New

S SERIES “DCP” 4-POST **HYDRAULIC REGENERATIVE TRIM PRESS**

QUALITY PRESSES WITH LONGEVITY !

WE HAVE BEEN MANUFACTURING NEW TRIM PRESSES SINCE 1968

Features S Series

- Platen machined from 1025 material
- Shut height adapters available
- 4-braid hydraulic hoses
- Safe, fully powered regenerative circuit
- Oil temperature & sight level gauges
- Cartridge valving manifold mounted
- Manual speed control
- Bolt on legs for shipping & rigging ease
- Ram speed 1 ft per second
- AB 500 processor
- Anti-drift cylinder seals.
- 5/8” t-slotted platens
- Solenoid indicator lights
- TEFC energy efficient pump motors
- Vickers double vane pump
- Chrome alloy tie bars
- Chrome plated trim cylinder piston rod
- One point tie bar lubrication
- **Operator safety pullouts with coincide anti-repeat**

Die Cast Press Mfg. Co., Inc.
Phone (269) 657-6060 - Fax (269) 657-9302



- Air operated safety ratchet and palm buttons
- Air operated parts unloading shuttle
- Keyence light curtains
- Auxiliary hydraulic valve and electrics for secondary operations such as side trimming, punching and piercing.
- Auto tie bar lubrication systems